



Since 1969

North America's **LARGEST** Manufacturer of Industrial **PRESSURE WASHERS**

OHW

Portable, Electric-Powered,
Diesel-Heated, Hot Water Pressure Washer

- Up to 4.2 GPM, 3000 PSI
- Belt-Drive Pump with 5-Year Warranty
- Sch. 80 Heating Coil
- Heavy-Duty Motor
- 120V to 575V



▲ Industrial-strength **Motor** and cast-iron, bushing **Pulleys** use a convenient 2-bolt pulley adjustment for easy maintenance and longer life; 2 notched "V" cogged belts, which operate cooler, connect the motor to the rugged **High-Pressure Pump** with three ceramic plungers and forged brass head with five-year warranty.

■ High-efficiency **Burner** is shielded by overhanging cover and features a **Fuel-Water Separator** for fuel pump protection.

■ Conveniently located **Control Panel** with magnetic starter (3 phase models) and anti-siphon detergent valve, which locks out air for precise soap metering.

■ 36 ft. of high-grade **Electrical Cord** with ground fault circuit interrupter on single-phase models for operator safety.

■ 50 ft. of steel-wire braid **High Pressure Hose** with 24-inch guard for burst protection.

■ Unique, slide-out **Service Platform** allows for easy access and servicing of pump and unloader.

■ High-heat steel inner wrap surrounds cold-rolled **Heating Coil** made of Schedule 80 steel pipe with five-year warranty.

■ Unique design allows access to the **Coil Wrap** within minutes by simply removing six bolts.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ Four quick-couple **Nozzles** are made of hardened stainless steel and mounted for ready access.



▲ Optional, E-Zee **Hose Reel** with compact, easy-wind design for tangle-free handling of hose (#4-02755030).

■ Built-in **Detergent Injector** for easy soap application

■ Rust-free **Float Tank** with stainless steel inlet filter for backflow protection.

■ Insulated, fatigue-free **Trigger Gun** with stainless steel, dual-lance **Variable Pressure Wand** make for easy cleaning and adjusting the pressure while washing.



■ Two-ply, tubed **Pneumatic Tires** make for easy maneuvering in any terrain; safety brake prevents rolling.

■ Many **Safety Features**, including a rupture disk and thermal pump protector to prevent the build up of excessive pressures or heat.

www.landa.com



LANDA[®]
PRESSURE WASHERS

North America's **LARGEST** Manufacturer of
Industrial **PRESSURE WASHERS**

OHW

Portable, Electric-Powered,
Diesel-Heated, Hot Water Pressure Washer

- Up to 4.2 GPM, 3000 PSI
- Belt-Drive Pump with 5-Year Warranty
- Sch. 80 Heating Coil
- Heavy-Duty Motor
- 120V to 575V



WHY CHOOSE LANDA'S OHW

The OHW is a value-packed line in *LANDA's* popular series of electric-powered, industrial hot water pressure washers with energy-efficient horizontal coils.

QUALITY: Packed with *LANDA* quality throughout, the OHW features top-of-the-line, tri-plunger high-pressure pump with 5-year warranty, Schedule 80 heating coil made of 1/2-inch pipe and a variety of engineering innovations that make this a service tech's dream.

PORTABILITY: The OHW is compact, easy to handle. Its leak-free, tubed, pneumatic tires make for easy maneuvering by the operator on any terrain. And its 36 feet of electrical cord provides additional mobility.

SAFETY: Certified to the rigid UL-1776 safety standards, the OHW also has many features that make it extremely safe, including motor thermal overload protection, rupture disk attached to the heating coil, thermal pump protector, flow-activated fuel shut-off switch, 24-inch hose guard for burst protection, and Ground Fault Circuit Interrupter on all single-phase models.

OHW Specifications

Part No.	GPM	PSI	Motor HP	Electrical	Amps	Pump	BTU / Hr	L x W x H	SHIP WT.
OHW3-11021D	2.8	1000	2	120V 1 ph	20	Tri-plunger	269,800	48" x 30.5" x 36.5"	530 lbs.
OHW4-20021A	4.2	2000	6	230V 1ph	29	Tri-plunger	404,700	48" x 30.5" x 36.5"	600 lbs.
OHW4-20021B	4.2	2000	6	230V 3ph	19	Tri-plunger	404,700	48" x 30.5" x 36.5"	600 lbs.
OHW4-20021C*	4.2	2000	6	460V 3ph	11	Tri-plunger	404,700	48" x 30.5" x 36.5"	600 lbs.
OHW4-30021A	3.5	3000	7.5	230V 1ph	36	Tri-plunger	309,560	48" x 30.5" x 36.5"	640 lbs.
OHW4-30021B	3.5	3000	7.5	230V 3ph	27.5	Tri-plunger	309,560	48" x 30.5" x 36.5"	640 lbs.
OHW4-30021C	3.5	3000	7.5	460V 3ph	17.5	Tri-plunger	309,560	48" x 30.5" x 36.5"	640 lbs.
OHW4-30021F*	3.5	3000	7.5	575V 3ph	14	Tri-plunger	309,560	48" x 30.5" x 36.5"	640 lbs.

* Also available are models configured to 208V 1ph and 3ph



Distributed by:

OPTIONS:

Part No.	Description
30-410	Tire upgrade to Pneumatic with Mag Wheels (Set of 4)
30-512	Stainless Steel Outer Coil Wrap
See Dealer	Automatic Start / Stop or Time Delay Shutdown are available upon request

www.landa.com